

KING SPRAYER SPECIFICATIONS



		CONTRACTOR KING 45:1	CONTRACTOR KING 60:1	CONTRACTOR KING 70:1
MODEL	Part Number	279005 Contractor King 45:1 (bare) 279006 Contractor King 45:1 (complete) 279007 Contractor King 45:1 (big 150)	279010 Contractor King 60:1 (bare) 279011 Contractor King 60:1 (complete) 279012 Contractor King 60:1 (big 150)	279013 Contractor King 70:1 (bare) 279014 Contractor King 70:1 (complete) 279022 Contractor King 70:1 (big 150)
TECHNICAL SPECIFICATIONS	Air Motor	XL 6500cc	XL 6500cc	XL 6500cc
	Pump Displacement	290cc	220cc	180cc
	Pump Type	Endurance	Endurance	Endurance
	Packing	UHMWPE/Leather	UHMWPE/Leather	UHMWPE/Leather
	Maximum Input Air Pressure Line	100 psi (7 bar)	100 psi (7 bar)	100 psi (7 bar)
	Max Working Pressure	4500 psi (310 bar)	6000 psi (414 bar)	7250 psi (500 bar)
	Max Flow Rate @ 60 Cycles/min	4.6 gpm (17.4 lpm)	3.4 gpm (12.9 lpm)	2.9 gpm (11 lpm)
	Compressor	User-supplied air compressor required. Minimum compressor rating of 50 dfm at 100 psi per 1 gpm sprayed	User-supplied air compressor required. Minimum compressor rating of 60 dfm at 100 psi per 1 gpm sprayed	User-supplied air compressor required. Minimum compressor rating of 70 dfm at 100 psi per 1 gpm sprayed
	Weight	145 lb	140 lb	135 lb
COMPLETE PACKAGES INCLUDED	Gun	Silver Plus	Silver Plus HP	Silver Plus HP
	Tip	XHD519	XHD519	XHD519
	Hoses	Xtreme Duty 4500 psi 3/8 in hose, 1/4 in whip	Xtreme Duty 7250 psi 3/8 in hose, 1/4 in whip	Xtreme Duty 7250 psi 3/8 in hose, 1/4 in whip
MANUAL	Sprayer Manual	3A9121	3A9121	3A9121
	Materials Sprayed	Primers, polyurethane top coats, Zinc coatings, Glass filled epoxies	High Solids, Mastics, Epoxies, Coal Tar, Silicone	High Solids, Mastics, Epoxies, Coal Tar, Silicone

