



		KING XL45-290	KING XL60-220	KING XL70-180	KING XL90-145
MODEL	Part Number	K45FH0 XL45 Heavy Duty Cart (bare)	K60FH0 XL60 Heavy Duty Cart (bare)	K70FH0 XL70 Heavy Duty Cart (bare)	K90FH0 XL90 Heavy Duty Cart (bare)
		K45NH0 XL45 Heavy Duty Cart No Filter (bare)	K60NH0 XL60 Heavy Duty Cart No Filter (bare)	K70NH0 XL70 Heavy Duty Cart No Filter (bare)	K90FH1 XL90 Heavy Duty Cart (complete)
		K45FL0 XL45 Light Weight Cart (bare)	K60FL0 XL60 Lightweight Cart (bare)	K70FL0 XL70 Lightweight Cart (bare)	
		K45FW0 XL45 Wall Mount (bare)	K60FW0 XL60 Wall Mount (bare)	K70FW0 XL70 Wall Mount (bare)	
		K45FH1 XL45 Heavy Duty Cart (complete)	K60FH1 XL60 Heavy Duty Cart (complete)	K70FH1 XL70 Heavy Duty Cart (complete)	
		K45NH1 XL45 Heavy Duty Cart No Filter (complete)	K60NH1 XL60 Heavy Duty Cart No Filter (complete)	K70NH1 XL70 Heavy Duty Cart No Filter (complete)	
		K45FW1 XL45 Wall Mount (complete)	K60FL1 XL60 Lightweight Cart (complete)	K70FL1 XL70 Lightweight Cart (complete)	
		K45FL1 XL45 Light Weight Cart (complete)	K60FW1 XL60 Wall Mount (complete)	K70FW1 XL70 Wall Mount (complete)	
TECHNICAL SPECIFICATIONS	Compressor	K45MH2 XL45 Heavy Duty Cart Max Life (complete)		K70MH2 XL70 Heavy Duty Cart Max Life (complete)	
		Air Motor	XL 6500cc	XL 6500cc	XL 6500cc
		Pump Displacement	290cc	220cc	180cc
		Pump Type	Xtreme	Xtreme	Xtreme
		Packing	UHMWPE/Leather	UHMWPE/Leather	UHMWPE/Leather
		Maximum Input Air Pressure Line	100 psi (7 bar)	100 psi (7 bar)	100 psi (7 bar)
		Max Working Pressure	4500 psi (310 bar)	6000 psi (414 bar)	7250 psi (500 bar)
		Max Flow Rate @ 60 Cycles/min	4.6 gpm (17.4 lpm)	3.4 gpm (12.9 lpm)	2.9 gpm (11 lpm)
COMPLETE PACKAGES INCLUDE	Compressor	User-supplied air compressor required. Minimum compressor rating of 50 cfm at 100 psi per 1 gpm sprayed	User-supplied air compressor required. Minimum compressor rating of 60 cfm at 100 psi per 1 gpm sprayed	User-supplied air compressor required. Minimum compressor rating of 70 cfm at 100 psi per 1 gpm sprayed	User-supplied air compressor required. Minimum compressor rating of 75 cfm at 80 psi per 1 gpm sprayed
		Gun	XTR5+	XTR7+	XTR7+
		Tip	XHD519	XHD519	XHD519
		Hoses	Xtreme Duty 4500 psi 3/8 in hose, 1/4 in whip	Xtreme Duty 7250 psi 3/8 in hose, 1/4 in whip	Xtreme Duty 7250 psi 3/8 in hose, 1/4 in whip
MANUAL	Materials Sprayed	Sprayer Manual	3A5422	3A5422	3A5422
			Primers, Polyurethane top coats, Zinc coatings, thin coatings	Primers, Polyurethane top coats,, Glass filled Epoxies	High Solids, Mastics, Epoxies, Coal Tar

KING HEAVY FLUID PACKAGES

PART #	MODEL	INCLUDES
26C891	King XL70-180 Heavy-fluid spray package	XHF™ Gun, 1/2 in x 50 ft Hose, 3/8 in x 6 ft Whip Hose, XHD429 Spray Tip, 10 gal SST Hopper
26C349	King XL70-180 Heavy-fluid Big 250 package	XHF Gun, 3/4 in x 200 ft Hose, 1/2 in x 50 ft Hose, Whip Hose, XHD531 Spray Tips, 10 gal SST Hopper

