

		 LINELAZER ES 500	 LINELAZER ES 1000	LINELAZER V ES 2000	LINELAZER 3400
SPECIFICATIONS	Maximum Tip Size	0.021	0.025	0.033	0.027
	Maximum psi (bar)	3300 (227)	3300 (227)	3300 (227)	3300 (227)
	Maximum gpm (lpm)	0.47 (1.8)	0.60 (2.3)	1.10 (4.1)	0.75 (2.8)
	Applications	Turf and Pavement	Turf and Pavement	Turf and Pavement	Turf and Pavement
	Honda GX Engine cc (hp)	N/A	N/A	N/A	120 (4.0)
	Weight lb (kg)	120 (54) - 1 Battery	300 (136) - 1 Battery 330 (150) - 2 Battery	350 (159) Standard 360 (163) HP Automatic	160 (73)
	Gun Support: 1 Gun 2 Guns 3 Guns 4 Guns 5 Guns	0.021 — — — —	0.025 — — — —	0.033 0.025 — — —	0.027 — — — —



SERIES TYPE		STANDARD	STANDARD	STANDARD	HP AUTOMATIC				STANDARD
MODEL	Part Number	25U546	25U674 – 1 Battery 25U676 – 2 Battery	25U678 – 2 Battery	25U679 – 2 Battery	25U680 – 2 Battery	25U683 – 2 Battery	25U684 – 2 Battery	25M224
	Gun(s)	Flex Plus 2 Manual	Flex Plus 2 Manual	Flex Plus 2 Manual	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus
INCLUDES	Hose	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	3/8 in x 22 ft (9.5 mm x 6.7 m) BlueMax II Airless				1/4 in x 50 ft (6.4 mm x 15 m) BlueMax II Airless	
	Laser				LazerGuide 1700 Start/Stop Laser				
	Laser						LazerGuide 2000 Laser-Guide Layout System		
	SwitchTip	LineLazer RAC 5	LineLazer RAC 5	LineLazer RAC 5				LineLazer RAC 5	
	Easy Out Filter	60 Mesh	60 Mesh	50 Mesh				60 Mesh	
PUMP	Type	ProConnect	ProConnect	QuikChange System				QuikChange System	
	Intake	QuikAccess	QuikAccess	QuikAccess				QuikAccess	
	Rod	Chromex	Chromex	Chromex				Chromex	
	Cylinder	Hardened SST	Hardened SST	Hardened Stainless Steel				Hardened SST	
	Packings	V-Max Blue	V-Max Blue	V-Max Blue				V-Max Blue	
TRACKING FUEL TANK	Tracking System	N/A	N/A	SmartControl				N/A	
	Fuel Capacity gal (ltrs)	N/A	N/A	N/A				0.66 (2.5)	

LINELAZER 130HS	LINELAZER V 3900	LINELAZER V 5900
0.037	0.036	0.043
3300 (227)	3300 (227)	3300 (227)
1.30 (4.9)	1.25 (4.7)	1.60 (6.0)
Turf and Pavement	Turf and Pavement	Turf and Pavement
120 (4.0)	120 (4.0)	160 (5.5)
263 (119)	230 (104) Standard Unit 240 (109) HP Automatic Units	250 (113) Standard Unit 266 (121) HP Automatic Units
0.037 0.029 — — —	0.036 0.025 — — —	0.043 0.029 — — —



STANDARD	STANDARD	HP AUTOMATIC				STANDARD	HP AUTOMATIC			
17H448	17H450	17H452	17H453	17U804	17U805	17H455	17H457	17H458	17U802	17U803
Flex Plus	Flex Plus 2 Manual	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus 2 Manual	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic
3/8 in x 22 ft (9.5 mm x 6.7 m) BlueMax II Airless	3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless					3/8 in x 50 ft (9.5 mm x 15 m) BlueMax II Airless				
		LazerGuide 1700 Start/Stop Laser					LazerGuide 1700 Start/Stop Laser			
				LazerGuide 2000 Laser-Guided Layout System					LazerGuide 2000 Laser-Guided Layout System	
LineLazer RAC 5	LineLazer RAC 5					LineLazer RAC 5				
50 Mesh	50 Mesh					50 Mesh				
QuikChange System	QuikChange System					QuikChange System				
QuikAccess	QuikAccess					QuikAccess				
Chromex	Chromex					Chromex				
Hardened SST	Hardened Stainless Steel					Hardened Stainless Steel				
V-Max Blue	V-Max Blue					V-Max Blue				
N/A	SmartControl					SmartControl				
0.66 (2.5)	0.66 (2.5)					0.95 (3.6)				



		LINELAZER V 200HS	LINELAZER V 200DC
SPECIFICATIONS	Maximum Tip Size	0.047	0.047
	Maximum psi (bar)	3300 (227)	3300 (227)
	Maximum gpm (lpm)	2.15 (8.1)	2.15 (8.1)
	Applications	Turf and Pavement	Turf and Pavement
	Honda GX Engine cc (hp)	200 (6.5)	200 (6.5)
	Weight lb (kg)	306 (139) Standard Unit 322 (146) HP Automatic Units 417 (153) HP Reflective Unit with Pressurized Bead System – 1 Tank	381 (173) Standard Unit 397 (180) HP Automatic Unit 492 (223) HP Reflective Units With Pressurized Bead System – 1 Tank
	Gun Support: 1 Gun 2 Guns 3 Guns 4 Guns 5 Guns	0.047 0.034 — — —	0.047 0.034 — — —



SERIES TYPE		STANDARD	HP AUTOMATIC		HP REFLECTIVE	STANDARD	HP AUTOMATIC	HP REFLECTIVE
MODEL *	Part Number	17H461	17H463	17H464	17H465	17Y231	17Y269	17Y270
INCLUDES	Gun(s)	Flex Plus 2 Manual	Flex Plus 1 Automatic, 1 Manual	Flex Plus 2 Automatic	Flex Plus 2 Automatic, PBS INSTALLED 1 TANK	Flex Plus 2 Manual	Flex Plus 2 Automatic	Flex Plus 2 Automatic, PBS INSTALLED 1 TANK
	Hose	3/8 in x 22 ft (9.5 mm x 6.7 m) BlueMax II Airless				2X 3/8 in x 12 ft (9.5 mm x 3.7 m) BlueMax II Airless		
	Laser		LazerGuide 1700 Start/Stop Laser				LazerGuide 1700 Start/Stop Laser	
	Laser							
	SwitchTip	LineLazer RAC 5				LineLazer RAC 5		
	Easy Out Filter	50 Mesh				50 Mesh		
PUMP	Type	QuikChange System				QuikChange System		
	Intake	QuikAccess				QuikAccess		
	Rod	Chromex				Chromex		
	Cylinder	Hardened Stainless Steel				Hardened Stainless Steel		
	Packings	V-Max Blue				V-Max Blue		
TRACKING FUEL TANK	Tracking System	SmartControl				SmartControl		
	Fuel Capacity gal (lts)	0.95 (3.6)				0.95 (3.6)		



		LINEDRIVER	LINEDRIVER HD	LINEDRIVER HD W/ ELECTRIC START	LINEDRIVER ES
MODEL	Part Number	262004	262005	25U474	25U670
SPECIFICATIONS	Operating Speed: Forward mph(km/h) Reverse mph (km/h)	to 10 (16) to 6 (10)	to 10 (16) to 6 (10)	to 10 (16) to 6 (10)	to 10 (16) to 6 (10)
	Engine Type	Honda GX	Honda GX	Briggs & Stratton Vanguard	Electric Motor
	Engine Size - cc (hp)	160 (5.5)	200 (6.5)	203 (6.5)	N/A
	Weight lb (kg)	265 (120)	275 (125)	275 (125)	355 (161)
	Engine Starting System	Manual Pull	ProStart	Electric Start	N/A



LINELAZER V 250SPS	LINELAZER V 250DC
0.055	0.055
3300 (227)	3300 (227)
2.50 (9.5)	2.50 (9.5)
Turf and Pavement	Turf and Pavement
390 (13.0) Electric Start	390 (13.0) Electric Start
666 (302) HP Automatic Units 778 (352) HP Reflective Unit with Pressure Bead System-2 Tanks	752 (341) HP Automatic Units 864 (392) HP Reflective Units with Pressure Bead System-2 Tanks
0.055 0.039 0.031 0.025 0.021	0.055 0.039 0.031 0.025 0.021



HP AUTOMATIC	HP REFLECTIVE				HP AUTOMATIC		HP REFLECTIVE			
17H467 - Honda 17H467V - Vanguard (CARB Approved)	Honda - 17J951 17J951V - Vanguard (CARB Approved)	Honda - 17H469	Honda - 25D345 25D345V - Vanguard (CARB Approved)	Honda - 25D340	Honda - 17H471 17H471V - Vanguard (CARB Approved)	Honda - 17H472	Honda - 17H473	Honda - 17H474 17H474V - Vanguard (CARB Approved)	Honda - 25D343	Honda - 25D344 25D344V - Vanguard - (CARB Approved)
Flex Plus 2 Automatic	Flex Plus 2 Automatic, PBS INSTALLED 1 TANK	Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS	Flex Plus 2 Automatic, PBS INSTALLED 1 TANK	Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS	Flex Plus 2 Automatic	Flex Plus 3 Automatic	Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS	Flex Plus 3 Automatic, PBS INSTALLED 2 TANKS	Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS	Flex Plus 3 Automatic, PBS INSTALLED 2 TANKS
3/8 in x 12 ft (9.5 mm x 3.7 m) BlueMax II Airless					2X 3/8 in x 12 ft (9.5 mm x 3.7 m) BlueMax II Airless					
			LazerGuide 3000 Long-Line Laser						LazerGuide 3000 Long-Line Laser	
LineLazer RAC 5					LineLazer RAC 5					
50 Mesh					50 Mesh					
QuikChange System					QuikChange System					
QuikAccess					QuikAccess					
Chromex					Chromex					
Hardened Stainless Steel					Hardened Stainless Steel					
V-Max Blue					V-Max Blue					
SmartControl					SmartControl					
1.40 (5.3)					1.40 (5.3)					

* All products, unless specified above are CARB approved.

Authorized Distributor



Blastline India Pvt. Ltd.
Blastline Corporate Chambers,
Kaloor- Perandoor Road, Elamakkara
Kochi, Kerala - 682026, IN



Website